



DARK ENERGY
SURVEY

PreCam Exposure Times

Douglas L. Tucker

DES-Calib/PreCam Telecon

2 December 2011



DARK ENERGY
SURVEY

The Equation

$$S/N = N_* / \text{sqrt}(N_* + N_{sky})$$

where

N_ and N_{sky} are in # of detected electrons.*

(Readnoise and dark current are ignored.)



DARK ENERGY
SURVEY

Original Estimates (2009)

**Baseline PreCam Survey Point-Source Magnitude Limits
(optimized to achieve S/N=50 at DES saturation + 1.5mag)**


Band	Exposure time [seconds]	PreCam saturation limit	PreCam mag limit S/N=50	Number of usable stars per sq deg (SGP)
g	36	12.8	17.8	186
r	51	13.2	17.8	265
i	65	13.4	17.7	344
z	162	14.1	17.5	317
Y	73	11.6	14.3	150



PreCam on Curtis-Schmidt with Original Folding Flat (50% Vignetting)

DARK ENERGY
SURVEY

Figure 0






PreCam on Curtis-Schmidt with Original Folding Flat (50% Vignetting)

DARK ENERGY
SURVEY

Figure 0






PreCam on Curtis-Schmidt with New Folding Flat (0% Vignetting)

DARK ENERGY
SURVEY

Figure 0






DARK ENERGY
SURVEY

PreCam on Curtis-Schmidt with New Folding Flat (0% Vignetting)


Figure 0





PreCam on CTIO/SMARTS 1m (0% Vignetting)


DARK ENERGY
SURVEY





PreCam on CTIO/SMARTS 1m (0% Vignetting)

DARK ENERGY
SURVEY





DARK ENERGY
SURVEY

Extra Slides